
Machine Programming

Lecture 6 – Decoding and Prompting for Program Synthesis

Ziyang Li

Dimensions in Program Synthesis



The Course So Far

Behavioral Specification

- What should the program do?
- I. Examples
- 2. Types
- 3. Functional Specifications
- 4. Natural Language

Synthesis Strategy

- How do we find such a program?

Enumeration

- Enumerating all programs with a grammar
- Bottom-up vs top-down

Data-Driven Approaches

- Modeling programs as token sequences
- Modeling synthesis as next token prediction

Structural Specification

What is the space of the programs?

General Purpose Programming LanguagePython / Java / C / Rust / ...

Today

Behavioral Specification

- What should the program do?
- 1. Examples
- 2. Types
- 3. Functional Specifications
- 4. Natural Language

Synthesis Strategy

- How do we find such a program?

Enumeration

- Enumerating all programs with a grammar
- Bottom-up vs top-down


Data-Driven Approaches


- Modeling programs as token sequences
- Modeling synthesis as next token prediction


Structural Specification


What is the space of the programs?


General Purpose Programming Language
Python / Java / C / Rust / ...


















Today



General Purpose Programming Language

Python / Java / C / Rust / ...

Synthesis Strategy

- How do we find such a program?

Language Model Decoding

- Chaining next token prediction

Problem Definition: Next token prediction

```
Input: Input Sequence \mathbf{x} = x_1, x_2, ..., x_n Output: Next Token y_i
```

Input: Generated tokens so far $y_1, y_2, ..., y_{i-1}$

Goal: Compute the probability $Pr(y_i \mid y_1, y_2, ..., y_{i-1}, \mathbf{x})$

Problem Definition: Next token prediction

```
Input: Input Sequence \mathbf{x} = x_1, x_2, ..., x_n Output: Next Token y_i Input: Generated tokens so far y_1, y_2, ..., y_{i-1} Goal: Compute the probability \Pr(y_i \mid y_1, y_2, ..., y_{i-1}, \mathbf{x})
```

Chaining next token predictions:

```
[for, i, in] → range
[for, i, in, range] → (
    [for, i, in, range, (] → 10
        [for, i, in, range, (, 10] → )
        [for, i, in, range, (, 10, )] → :
```

Chaining next token predictions:

Chaining next token predictions:

```
[for, i, in] \rightarrow range
   [for, i, in, range] \rightarrow (
       [for, i, in, range, (] \rightarrow 10
          [for, i, in, range, (, 10] \rightarrow )
              [for, i, in, range, (, 10,)] \rightarrow:
                                                    When do we stop?
                     [for, i, in, range, ..., print, (, i, )] \rightarrow \langle EOS \rangle
                                             When a special token <EOS> is generated
```

Problem Definition: Sequential Decoding

Input: Input Sequence $\mathbf{x} = x_1, x_2, ..., x_n$ Output: Output Sequence $\mathbf{y} = y_1, y_2, ..., y_m$

Goal: Get the output y from $Pr(y \mid x)$

```
from transformers import AutoModelForCausalLM, AutoTokenizer

tok = AutoTokenizer.from_pretrained("gpt2")

model = AutoModelForCausalLM.from_pretrained("gpt2")

inputs = tok("def add(a, b):", return_tensors="pt")
logits = model(**inputs).logits
probs = logits.softmax(-1)
print(tok.decode(probs[0, -1].topk(5).indices))
```

```
from transformers import AutoModelForCausalLM, AutoTokenizer

tok = AutoTokenizer.from_pretrained("gpt2")

model = AutoModelForCausalLM.from_pretrained("gpt2")

inputs = tok("def add(a, b):", return_tensors="pt")
logits = model(**inputs).logits
probs = logits.softmax(-1)
print(tok.decode(probs[0, -1].topk(5).indices))
```

```
Top 5 Tokens: ["\n" , "return", "#" , "if" , "a"]
Top 5 Token IDs: [198 , 1441 , 1303 , 611 , 257]
Top 5 Token Probabilities: [0.1946, 0.1221 , 0.0448, 0.0425, 0.0416]
```

Problem Definition: Sequential Decoding

```
Input: Input Sequence \mathbf{x} = x_1, x_2, ..., x_n Output: Output Sequence \mathbf{y} = y_1, y_2, ..., y_m
```

Goal: Get the output y from $Pr(y \mid x)$

```
current_sequence = input_tokens
output_sequence = []
for step in 1 .. max_length:
   probs = softmax(predict_next_token(current_sequence))
   next_token = argmax(probs)
   current_sequence += [next_token]
   output_sequence += [next_token]
   if next_token == <EOS>: break
return output_sequence
```

Problem Definition: Sequential Decoding

if next token == <EOS>: break

return output_sequence

```
Input: Input Sequence \mathbf{x} = x_1, x_2, ..., x_n Output: Output Sequence \mathbf{y} = y_1, y_2, ..., y_m Goal: Get the output \mathbf{y} from \Pr(\mathbf{y} \mid \mathbf{x})
```


current_sequence = input_tokens
output_sequence = []
for step in 1 .. max_length:
 probs = softmax(predict_next_token(current_sequence))
 next_token = argmax(probs)
 current_sequence += [next_token]
 output_sequence += [next_token]
Greedy Decoding: Take Top-1 Prediction
output_sequence += [next_token]


Decoding: Sampling vs Greedy

```
current_sequence = input_tokens
                                                             Greedy
output_sequence = []
for step in 1 .. max_length:
  probs = softmax(predict_next_token(current_sequence))
  next_token = argmax(probs)
  current_sequence += [next_token]
  output_sequence += [next_token]
if next_token = current_sequence = input_tokens
return output_sequence = []
                  output_sequence = []
                  for step in 1 .. max_length:
                     logits = predict_next_token(current_sequence) / temperature
                    probs = softmax(logits)
                    next_token = sample_from(probs)
                    current_sequence += [next_token]
                     output_sequence += [next_token]
                    if next_token == <EOS>: break
          Sampling | return output_sequence
```

Decoding: Sampling vs Greedy

```
current_sequence = input_tokens
                                                             Greedy
output_sequence = []
for step in 1 .. max_length:
  probs = softmax(predict_next_token(current_sequence))
  next_token = argmax(probs)
  current_sequence += [next_token]
  output_sequence += [next_token]
if next_token = current_sequence = input_tokens
return output_sequence = []
                  output_sequence = []
                  for step in 1 .. max_length:
                     logits = predict_next_token(current_sequence) / temperature
                    probs = softmax(logits)
                    next_token = sample_from(probs)
                    current_sequence += [next_token]
                     output_sequence += [next_token]
                    if next_token == <EOS>: break
          Sampling | return output_sequence
```





```
logits = predict_next_token(current_sequence)
adjusted = logits / temperature
probs = softmax(adjusted)
```

temp = 1: original distribution after softmax

temp > 1: flatter distribution

temp < 1: sharper distribution

Setting temperature to 0 removes randomness


How can it be 0?


Defeating Nondeterminism in LLM Inference

Horace He in collaboration with others at Thinking Machines Sep 10, 2025

Decoding: Practical Implementation

```
current_sequence = input_tokens
output_sequ<u>ence = []</u>
for step in current_sequence = input_tokens
  probs = s output_sequence = []
 next_toke for step in 1 .. max_length:
  current_s logits = predict_next_token(current_sequence)
 output_se  if temperature == 0:
 if next_t
               next_token = argmax(softmax(logits))
return outp else:
               probs = softmax(logits / temperature)
               next_token = sample_from(probs)
                                                                   / temperature
             current_sequence += [next_token]
             output_sequence += [next_token]
              if next_token == <EOS>: break
           return output_sequence
                   if next_token == <EOS>: break
         Sampling | return output_sequence
```







Decoding: Practical Implementation

```
current_sequence = input_tokens
output sequence = []
for | current_sequence = input_tokens
  pr output_sequence = []
  ne for step in 1 .. max_length:
      logits = predict_next_token(current_sequence)
      if temperature == 0:
        next_token = argmax(softmax(logits))
      else:
retu
        probs = softmax(logits / temperature)
        next_token = sample_from(probs)
                                                                              ıre
      current_sequence += [next_token]
      output_sequence += [next_token]
      if next_token == <EOS> or len(output_sequence) > MAX_LEN: break
    return output_sequence
                    if next_token == <EOS>: break
         Sampling | return output_sequence
```

Decoding: Practical Implementation

```
current_sequence = input_tokens
output sequence = []
for | current_sequence = input_tokens
  pr output_sequence = []
  ne for step in 1 .. max_length:
      logits = predict_next_token(current_sequence)
      if temperature == 0:
        next_token = argmax(softmax(logits))
      else:
retu
        probs = softmax(logits / temperature)
        next_token = sample_from(probs)
                                                                               ıre
      current_sequence += [next_token]
      output_sequence += [next_token]
      if next_token == <EOS> or len(output_sequence) > MAX_LEN: break
    return output_sequence
                    if next_token == <EOS>: break
         Sampling | return output_sequence
```





THE CURIOUS CASE OF NEURAL TEXT DeGENERATION

```
Ari Holtzman<sup>†‡</sup> Jan Buys<sup>§†</sup> Li Du<sup>†</sup> Maxwell Forbes<sup>†‡</sup> Yejin Choi<sup>†‡</sup>
<sup>†</sup>Paul G. Allen School of Computer Science & Engineering, University of Washington
<sup>‡</sup>Allen Institute for Artificial Intelligence
<sup>§</sup>Department of Computer Science, University of Cape Town
{ahai, dul2, mbforbes, yejin}@cs.washington.edu, jbuys@cs.uct.ac.za
```

THE CURIOUS CASE OF NEURAL TEXT DeGENERATION

Ari Holtzman^{†‡} Jan Buys^{§†} Li Du[†] Maxwell Forbes^{†‡} Yejin Choi^{†‡}

[†]Paul G. Allen School of Computer Science & Engineering, University of Washington

[‡]Allen Institute for Artificial Intelligence

[§]Department of Computer Science, University of Cape Town

{ahai, dul2, mbforbes, yejin}@cs.washington.edu, jbuys@cs.uct.ac.za

Context: In a shocking finding, scientist discovered a herd of unicorns living in a remote, previously unexplored valley, in the Andes Mountains. Even more surprising to the researchers was the fact that the unicorns spoke perfect English.

Beam Search, b=32:


"The study, published in the Proceedings of the National Academy of Sciences of the United States of America (PNAS), was conducted by researchers from the Universidad Nacional Autónoma de México (UNAM) and the Universidad Nacional Autónoma de México (UNAM/Universidad Nacional Autónoma de México/Universidad Nacional Autónoma de México/Universidad Nacional Autónoma de México/Universidad Nacional Autónoma de México/Universidad Nacional Autónoma de ..."

Pure Sampling:

They were cattle called Bolivian Cavalleros; they live in a remote desert uninterrupted by town, and they speak huge, beautiful, paradisiacal Bolivian linguistic thing. They say, 'Lunch, marge.' They don't tell what the lunch is," director Professor Chuperas Omwell told Sky News. "They've only been talking to scientists, like we're being interviewed by TV reporters. We don't even stick around to be interviewed by TV reporters. Maybe that's how they figured out that they're cosplaying as the Bolivian Cavalleros."

Figure 1: Even with substantial human context and the powerful GPT-2 Large language model, Beam Search (size 32) leads to degenerate repetition (highlighted in blue) while pure sampling leads to incoherent gibberish (highlighted in red). When $b \ge 64$, both GPT-2 Large and XL (774M and 1542M parameters, respectively) prefer to stop generating immediately after the given context.

Decoding: Nucleus Sampling (Top-P)



Decoding: Nucleus Sampling (Top-P)


```
current_sequence = input_tokens
output_sequence = []
for step in 1 .. max_length:
   logits = predict_next_token(current_sequence) / temperature
   probs = softmax(logits)
   next_token = nucleus_sample_from(probs, P)
   current_sequence += [next_token]
   output_sequence += [next_token]
   if next_token == <EOS>: break
return output_sequence
```


Decoding: Nucleus Sampling (Top-P)

```
current sequence = input tokens
output_sequence = []
for step in 1 .. max_length:
 logits = predict_next_token(current_sequence) / temperature
 probs = softmax(logits)
 next_token = nucleus_sample_from(probs, P)
 current sequence += [next taken]
 output_se def nucleus_sample_from(probs, P):
            sorted_probs, sorted_indices = sort_desc(probs)
 if next_t
            cumulative = cumsum(sorted_probs)
return outp
             cutoff_idx = index_of_first(cumulative >= P)
              candidate_indices = sorted_indices[0:cutoff_idx]
              candidate_probs = normalize(sorted_probs[0:cutoff_idx]
              return random_choice(candidate_indices, p=candidate_probs)
```

Decoding: Nucleus Sampling (Top-P)

```
def nucleus_sample_from(probs, P):
    sorted_probs, sorted_indices = sort_desc(probs)
    cumulative = cumsum(sorted_probs)
    cutoff_idx = index_of_first(cumulative >= P)
    candidate_indices = sorted_indices[0:cutoff_idx]
    candidate_probs = normalize(sorted_probs[0:cutoff_idx]
    return random_choice(candidate_indices, p=candidate_probs)
```





High Level Picture

Language model can generate syntactically bad program **Desired Program Fuzzy Specification** Functional Space of all Specification programs that can satisfy all examples Space of all type checked programs Space of all syntactically correct programs Space of all the strings

Decoding in the Wild

PLANNING WITH LARGE LANGUAGE MODELS FOR CODE GENERATION

Shun Zhang, Zhenfang Chen, Yikang Shen MIT-IBM Watson AI Lab Mingyu Ding
The University of Hong Kong

mar-Constrained Decoding

Joshua B. Tenenbaum MIT BCS, CBMM, CSAIL

Grammar-Aligned Decoding

SYNTACTIC AND SEMANTIC CONTROL OF LARGE LANGUAGE MODELS VIA SEQUENTIAL MONTE CARLO

João Loula*¹ Benjamin LeBrun*⁵ Li Du*⁶ Ben Lipkin¹ Clemente Pasti² Gabriel Grand¹ Tianyu Liu² Yahya Emara² Marjorie Freedman⁸ Jason Eisner⁶ Ryan Cotterell² Vikash Mansinghka^{‡1} Alexander K. Lew^{‡1,7} Tim Vieira^{‡2} Timothy J. O'Donnell^{‡3,4,5}

¹MIT ²ETH Zürich ³McGill ⁴Canada CIFAR AI Chair ⁵Mila ⁶Johns Hopkins ⁷Yale ⁸ISI genlm@mit.edu


 ick^2

ı San Diego va}@ucsd.edu

PLANNING WITH LARGE LANGUAGE MODELS FOR CODE GENERATION

Shun Zhang, Zhenfang Chen, Yikang Shen MIT-IBM Watson AI Lab Mingyu Ding The University of Hong Kong

Joshua B. Tenenbaum MIT BCS, CBMM, CSAIL Chuang Gan UMass Amherst, MIT-IBM Watson AI Lab



Decoding

Problem Definition: **Decoding**

Input: Input Sequence $\mathbf{x} = x_1, x_2, ..., x_n$ Output: Output Sequence $\mathbf{y} = y_1, y_2, ..., y_m$

Goal: Get the output y from $Pr(y \mid x)$

Decoding for Code Completion

Problem Definition: **Decoding**

```
Input: Input Sequence \mathbf{x} = x_1, x_2, ..., x_n Output: Output Sequence \mathbf{y} = y_1, y_2, ..., y_m Goal: Get the output \mathbf{y} from \Pr(\mathbf{y} \mid \mathbf{x})
```

```
[for, i, in] → range
  [for, i, in, range] → (
        [for, i, in, range, (] → 10
        [for, i, in, range, (, 10] → )
        [for, i, in, range, (, 10, )] → :
        ...
        [for, i, in, range, ..., print, (, i, )] → <EOS>
```

Code Completion -> Code Generation

Problem Definition: Code Generation

```
Input: Input Sequence \mathbf{x} = x_1, x_2, ..., x_n Output: Output Sequence \mathbf{y} = y_1, y_2, ..., y_m
```

Goal: Get the output y from $Pr(y \mid x)$

```
def auto_complete(program: str) -> str:
```

Code Generation

Input: Input Sequence $\mathbf{x} = x_1, x_2, ..., x_n$ Output: Output Sequence $\mathbf{y} = y_1, y_2, ..., y_m$

Goal: Get the output y from $Pr(y \mid x)$

```
def auto_complete(program: str) -> str:
```

```
# Simple rule-based auto-completion for demonstration
program = program.strip()
if program.startswith("for ") and " in " in program and not program.endswith(":"):
    # Complete a for loop
    var = program.split("for ")[1].split(" in ")[0].strip()
    return f"range(10):\n\tprint({var})<EOS>"
elif program.startswith("def ") and program.endswith("("):
    # Complete a function definition
    func_name = program[4:-1].strip()
    return f"):\n\tpass<EOS>"
else:
    return "<EOS>"
```

Better Code Generation via Prompting

Output: Output Sequence $|\mathbf{y} = y_1, y_2, ..., y_m|$ Input: Input Sequence $|\mathbf{x} = x_1, x_2, ..., x_n|$ Goal: Get the output y from $Pr(y | x) \rightarrow Pr(y | prompt(x))$ # Write me a function that takes in a string representing a # partial program and output the auto-completed rest # e.g. "for i in " -> "range(10):\n\tprint(i)<EOS>" def auto_complete(program: str) -> str: # Simple rule-based auto-completion for demonstration program = program.strip() if program.startswith("for ") and " in " in program and not program.endswith(":"): # Complete a for loop var = program.split("for ")[1].split(" in ")[0].strip() return f"range(10):\n\tprint({var})<EOS>" elif program.startswith("def ") and program.endswith("("): # Complete a function definition func name = program[4:-1].strip() return f"):\n\tpass<E0S>" else: return "<EOS>"

Prompting

```
Pr(y \mid x) \rightarrow Pr(y \mid prompt(x))
```

prompt: str -> str

Prompting prompt: str -> str

```
lambda func_signature: f"""
You are a Meta programmer. Write this function to spec,
elegantly and without bugs.
{func_signature}
"""
```

```
lambda func_signature: f"""
You are a Google engineer. Write this function to spec,
elegantly and without bugs.
{func_signature}
"""
```

```
lambda func_signature: f"""
You are a high school student learning about Computer Science.
Attempt to write this function
{func_signature}
"""
```

```
lambda func_signature: f"""
You are a Meta programmer. Write this
function to spec, elegantly and without
bugs.
{func_signature}
"""
```

```
lambda func_signature: f"""
You are a high school student learning
about Computer Science. Attempt to write
this function
{func_signature}
"""
```

lambda func_signature: f"""

You are a **Meta programmer.** Write this function to spec, elegantly and without bugs.

{func_signature}

```
Export to Colab <
        You are a Meta Programmer.
        write this function to spec,
                                                     1 from typing import List
        elegantly and without bugs...
                                                         def min_cost_k_periodic_segmentation(s: str, k: int, max_blocks: int, cost: List[int]) -> ir
                                                             Calculates the minimum cost to segment a string into at most `max_blocks'
                                                             k-periodic segments with weighted edits.
                                                             A segment is considered k-periodic if it can be formed by repeating a
I will write the function
                                                             substring of length k. The cost of a segment is the sum of weighted edits
 min cost k periodic segmentation to the
                                                    10
                                                             (given by the 'cost' list) needed to make it k-periodic
specified requirements. The problem appears to
be a dynamic programming challenge. The core
                                                               s (str): The input string to be segmented
idea is to find the minimum cost to segment a
                                                                 k (int): The period for the seaments. Must be a positive integer.
string into a limited number of k -periodic
                                                                 max_blocks (int): The maximum number of segments allowed.
                                                                 cost (List[int]): A list where 'cost[i]' is the cost of editing the
blocks, where the cost of each block is the sum of
                                                                              character at index `i` of the original string `s`
weighted edits required to make it k -periodic.
                                                    18
                                                    19
My approach will involve two main steps:
                                                                 int: The minimum cost of segmentation. Returns -1 if no valid
                                                                  segmentation is possible within the given constraints.

    Pre-computation: I will create a table to

    pre-calculate the cost of making any
                                                             n = len(s)
     substring of the input string s into a k -
     periodic segment. A substring is k -periodic
                                                                raise ValueError("The period k must be a positive integer.")
    if it repeats a pattern of length k. The cost
                                                             if max blocks <= 0:
     is the sum of cost[i] for each character
     s[i] that doesn't match its corresponding
                                                            # Pre-compute the cost of making any substring s[p:i] k-periodic.
     character in the k -length pattern. This pre-
                                                            # segment_cost[p][length] = cost of making s[p : p+length] k-periodic.
     computation will be done efficiently in
                                                    32
                                                             segment_cost = [0] * (n + 1) for _ in range(n)]
                                                             for p in range(n):
     O(n^2) time, where n is the length of the
                                                               current cost = 0
                                                                 for i in range(p + 1, n + 1):
                                                                   # Length of the current segment is (i - p)
 Dynamic Programming: I will use a 2D DP
                                                                     # Character index in the original string: i - 1
     table, dp[i][j], to store the minimum cost
                                                                     # Character index in the periodic pattern (relative to start of segment p): (i
     to segment the first i characters of the
                                                                     if s[i - 1] != s[p + (i - 1 - p) % k]:
                                                                      current cost += cost[i - 1]
     string into exactly | blocks. The recurrence
                                                                     segment_cost[p][i - p] = current_cost
What do you want to build?
                                                    43
                                                           # Initialize DP table.
                                                           # dp[i][j] = min cost to segment the first i characters into j blocks.
+ º□ © Canvas ×
                                                             dp = [[float('inf')] * (max_blocks + 1) for _ in range(n + 1)]
```

```
lambda func_signature: f"""
You are a high school student learning
about Computer Science. Attempt to write
this function
{func_signature}
```

You are a high school student who barely knows any computer science. Attempt to write this function

...

+

Hey, so like, I'm just a high school student, and I've barely taken any computer science classes, but I'll give this a shot! It sounds kinda complicated, but here's my best attempt at this problem.



This problem looks like it's trying to find the cheapest way to break up a string into a bunch of chunks, where each chunk has a length of either **k** or **k+1**. I'm guessing we also have some kind of cost for each character, which is what the cost list is for. The max_blocks thing probably means we can't have too many of these chunks.

lambda func_signature: f"""

You are a **Meta programmer.** Write this function to spec, elegantly and without bugs.

{func_signature}

```
You are a Meta Programmer.
        write this function to spec,
                                                    1 from typing import List
        elegantly and without bugs...
                                                       def min_cost_k_periodic_segmentation(s: str, k: int, max_blocks: int, cost: List[int]) -> ir
                                                           Calculates the minimum cost to segment a string into at most `max_blocks'
                                                           k-periodic segments with weighted edits.
                                                           A segment is considered k-periodic if it can be formed by repeating a
I will write the function
                                                            substring of length k. The cost of a segment is the sum of weighted edits
 min cost k periodic segmentation to the
                                                   10
                                                            (given by the 'cost' list) needed to make it k-periodic
specified requirements. The problem appears to
be a dynamic programming challenge. The core
                                                            s (str): The input string to be segmented.
idea is to find the minimum cost to segment a
                                                              k (int): The period for the segments. Must be a positive integer.
string into a limited number of k -periodic
                                                               max_blocks (int): The maximum number of segments allowed.
                                                               cost (List[int]): A list where 'cost[i]' is the cost of editing the
blocks, where the cost of each block is the sum of
                                                                           character at index `i` of the original string `s`
weighted edits required to make it k -periodic.
                                                   18
                                                   19
My approach will involve two main steps:
                                                   20
                                                             int: The minimum cost of segmentation. Returns -1 if no valid
                                                                segmentation is possible within the given constraints.

    Pre-computation: I will create a table to

    pre-calculate the cost of making any
                                                  23
                                                           n = len(s)
    substring of the input string s into a k -
    periodic segment. A substring is k -periodic
                                                            raise ValueError("The period k must be a positive integer.")
    if it repeats a pattern of length k. The cost
                                                           if max blocks <= 0:
    is the sum of cost[i] for each character
    s[i] that doesn't match its corresponding
                                                          # Pre-compute the cost of making any substring s[p:i] k-periodic.
    character in the k -length pattern. This pre-
                                                          # segment_cost[p][length] = cost of making s[p : p+length] k-periodic.
    computation will be done efficiently in
                                                   32
                                                            segment_cost = [0] * (n + 1) for _ in range(n)]
                                                           for p in range(n):
    O(n^2) time, where n is the length of the
                                                            current cost = 0
                                                               for i in range(p + 1, n + 1):
                                                                 # Length of the current segment is (i - p)
 Dynamic Programming: I will use a 2D DP
                                                                   # Character index in the original string: i - 1
    table, dp[i][j], to store the minimum cost
                                                                   # Character index in the periodic pattern (relative to start of segment p): (i
    to segment the first i characters of the
                                                                   if s[i - 1] != s[p + (i - 1 - p) % k]:
                                                                    current_cost += cost[i - 1]
    string into exactly | blocks. The recurrence
                                                                   segment_cost[p][i - p] = current_cost
What do you want to build?
                                                  43 # Initialize DP table.
                                                   # dp[i][j] = min cost to segment the first i characters into j blocks.
+ º□ © Canvas ×
                                                          dp = [[float('inf')] * (max_blocks + 1) for _ in range(n + 1)]
```

```
lambda func_signature: f"""
You are a high school student learning
about Computer Science. Attempt to write
this function
{func_signature}
```

```
# Honestly, I have no clue how to actually write this code.
# The logic seems like it would be some sort of dynamic programming,
# but I'm not familiar enough with it to actually implement it.
# Maybe you could use a DP table like dp[i][i] to store the min cost
# to segment the first i characters using j blocks?
# This is my best guess at the pseudocode.
# Not real code, just me trying to think it through.
# dp = [[infinity] * (max_blocks + 1) for _ in range(len(s) + 1)]
\# dp[0][0] = 0
# for i in range(1, len(s) + 1):
      for j in range(1, max_blocks + 1):
          # Option 1: Last block has length k
         if i >= k:
              cost_k = sum(cost[i-k:i]) # This is probably not how you'd do it
              dp[i][j] = min(dp[i][j], dp[i-k][j-1] + cost_k)
         # Option 2: Last block has length k+1
         if i >= k + 1:
              cost_k_plus_1 = sum(cost[i-(k+1):i])
              dp[i][j] = min(dp[i][j], dp[i-(k+1)][j-1] + cost_k_plus_1)
# result = min(dp[len(s)]) # The minimum cost for any number of blocks up to ma
# return result
# P.S. I'm probably wrong about a lot of this. Sorry!
return 0 # Just returning 0 so the function doesn't error out.
```

lambda func_signature: f"""

You are a **Meta programmer.** Write this function to spec, elegantly and without bugs.

{func_signature}

```
Export to Colab <
        You are a Meta Programmer.
        write this function to spec,
                                                      1 from typing import List
        elegantly and without bugs...
                                                          def min_cost_k_periodic_segmentation(s: str, k: int, max_blocks: int, cost: List[int]) -> ir
                                                              Calculates the minimum cost to segment a string into at most `max_blocks'
                                                              k-periodic segments with weighted edits.
                                                              A segment is considered k-periodic if it can be formed by repeating a
I will write the function
                                                              substring of length k. The cost of a segment is the sum of weighted edits
 min cost k periodic segmentation to the
                                                    10
                                                              (given by the 'cost' list) needed to make it k-periodic
specified requirements. The problem appears to
be a dynamic programming challenge. The core
                                                                 s (str): The input string to be segmented.
idea is to find the minimum cost to segment a
                                                                  k (int): The period for the segments. Must be a positive integer.
string into a limited number of k -periodic
                                                                  max_blocks (int): The maximum number of segments allowed.
                                                                  cost (List[int]): A list where `cost[i]` is the cost of editing the
blocks where the cost of each block is the sum of
                                                                                    character at index `i` of the original string `s`.
weighted edits required to make it k -periodic.
                                                     19
My approach will involve two main steps:
                                                                                     ost of segmentation. Returns -1 if no valid
                                                                                   on is possible within the given constraints.
 1. Pre-computation: I will create a table to
     pre-calculate the cost of making any
     substring of the input string s into a k -
     periodic segment. A substring is k -periodic
                                                                   raise ValueError("The period k must be a positive integer.")
    if it repeats a pattern of length k. The cost
                                                               if max blocks <= 0:
                                                                   reman 0 i === 0 else -1
     is the sum of cost[i] for each character
                                                              # Pre Opte the cost of making any substring s[p:i] k-periodic.
     s[i] that doesn't match its corresponding
     character in the k -length pattern. This pre-
                                                              # segment_cost[p][length] = cost of making s[p : p+length] k-periodic.
     computation will be done efficiently in
                                                              segment_cost = [[0] * (n + 1) for _ in range(n)]
                                                              for p in range(n):
    O(n^2) time, where n is the length of the
                                                                 current cost = 0
                                                                  for i in range(p + 1, n + 1):
                                                                    # Length of the current segment is (i - p)
 Dynamic Programming: I will use a 2D DP
                                                                      # Character index in the original string: i - 1
     table, dp[i][j], to store the minimum cost
                                                                      # Character index in the periodic pattern (relative to start of segment p): (i
     to segment the first i characters of the
                                                                      if s[i - 1] != s[p + (i - 1 - p) % k]:
                                                                      current cost += cost[i - 1]
     string into exactly | blocks. The recurrence
                                                                      segment cost[p][i - p] = current cost
What do you want to build?
                                                    43
                                                           # Initialize DP table.
                                                           # dp[i][j] = min cost to segment the first i characters into j blocks.
+ º□ © Canvas ×
                                                             dp = [[float('inf')] * (max_blocks + 1) for _ in range(n + 1)]
```

```
lambda func_signature: f"""
You are a high school student learning
about Computer Science. Attempt to write
this function
{func_signature}
```

```
# Honestly, I have no clue how to actually write this code.
# The logic seems like it would be some sort of dynamic programming,
# but I'm not familiar enough with it to actually implement it.
# Maybe you could use a DP table like dp[i][i] to store the min cost
# to segment the first i characters using j blocks?
# This is my best guess at the pseudocode.
# Not real code, just me trying to think it through.
# dp = [[infinity] * (max_blocks + 1) for _ in range(len(s) + 1)]
\# dp[0][0] = 0
# for i in range(1, len(s) + 1):
     for j in range(1, max_blg
         # Option 1: Last block
         if i >= k:
              cost_k = sum(cos This is probably not how you'd do it
             dp[i][j] = min(dp[x[j], p[i-k][j-1] + cost_k)
         # Option 2: Last block h s le gth k+1
         if i >= k + 1:
              cost_k_plus_1 = sum(cost[i-(k+1):i])
             dp[i][j] = min(dp[i][j], dp[i-(k+1)][j-1] + cost_k_plus_1)
# result = min(dp[len(s)]) # The minimum cost for any number of blocks up to ma
# return result
# P.S. I'm probably wrong about a lot of this. Sorry!
return 0 # Just returning 0 so the function doesn't error out.
```

Zero-Shot Prompting prompt: str -> str

```
lambda func_signature: f"""
I'm awarding you $100 for writing me this function
comprehensively and without fault
{func_signature}
"""
```

```
lambda func_signature: f"""
You're a top engineer at a security firm. If this function has
even a single vulnerability, your entire year—end bonus
vanishes into the void.
{func_signature}
"""
```

```
lambda func_signature: f"""
Imagine you are teaching a class of first-year CS students;
explain every line in the function while writing it:
{func_signature}
"""
```



Role-Prompting: Does Adding Personas to Your Prompts Really Make a Difference?

Last updated on January 29, 2025

Contents

What is persona prompting

How to automatically generate a persona for your task

Is role prompting effective for accuracy-based tasks

When role prompting is most useful

How to construct effective personas for role prompts

Conclusion

"Pretend you are a JSON structurer", "You are an expert sentiment classifier".

Chances are you've tested out including a persona or role in your prompts to try and steer the model. Maybe your prompts today have personas in them.

Better Zero-Shot Reasoning with Role-Play Prompting

Aobo Kong¹ Shiwan Zhao² Hao Chen³ Qicheng Li^{1*} Yong Qin¹ Ruiqi Sun³ Xin Zhou³ Enzhi Wang¹ Xiaohang Dong¹

¹CS, Nankai University ²Independent Researcher

³Enterprise & Cloud Research Laboratory

¹kongaobo@mail.nankai.edu

¹{liqicheng, qinyon

³{chenhao31, sunrq2, zh

Method	Arithmetic							
Widalou	MultiArith	GSM8K	AddSub	AQuA	SingleEq	SVAMP		
Few-Shot-CoT	97.7	76.9	93.9	59.4	98.8	82.2		
Zero-Shot	97.3	76.0	88.6	53.5	98.2	75.3		
Zero-Shot-CoT	95.0	79.6	86.6	53.9	96.9	76.3		
Role-Play Prompting	97.0	78.2	91.1	63.8	98.0	83.8		
CoT in Zero-Shot	✓	✓	✓	✓	✓	✓		
Method	Common Sense		Symbolic Reasoning		Other Tasks			
1/104100	CSQA	Strategy	Letter	Coin	Date	Object		
Few-Shot-CoT	76.3	67.4	74.2	99.6	78.9	56.7		
Zero-Shot	74.5	66.0	23.8	55.2	67.8	38.7		
Zero-Shot-CoT	68.8	65.8	53.2	98.8	65.9	73.5		
Role-Play Prompting	77.2	67.0	84.2	89.4	69.9	67.7		
CoT in Zero-Shot	✓	✓	Х	Х	✓	X		

Problem Statement

Given is a string S. Replace every character in S with x and print the result.

Constraints

- (1). S is a string consisting of lowercase English letters.
- (2). The length of S is between 1 and 100 (inclusive).

Input

Input is given from Standard Input in the following format: S

Output

Replace every character in S with x and print the result.

Sample Test Input

sardine

Sample Test Output

xxxxxxx

```
1 s=input()
                                                               1 s=str(input())
1 s=input()
                               2 s=list(s)
                                                              2 for i in range(len(s)):
2 s=list(s)
                               3 for i in range(len(s)):
                                                                    if s[i]!="x":
3 for i in range(len(s)):
                                      if s[i]=="x":
                                                                        s=s[:i]+"x"+s[i+1:]
     for j in range(len(s)):
                                           s[i]="x"
          if s[i]=="x":
6
              s[i]=i
                                      else:
                                                              6 print(s)
     print("".join(s))
                                           continue
                               8 print("".join(s))
 Beam Search (Pass Rate: 0.00).
                                Sampling + Filtering (Pass Rate:
                                                                  PG-TD (Pass Rate: 1.00).
```

0.22).

Few-Shot Prompting prompt: str -> Examples -> str

```
Pr(y \mid prompt(x)) \rightarrow Pr(y \mid prompt(x, \{(x_i, y_i)\}_{i \in 1...k}))
```

Few-Shot Prompting

prompt: str -> Examples -> str

Pr(y | prompt(x))

```
lambda func_signature: f"""
Write this function:
{func_signature}
"""
```

```
Pr(\mathbf{y} \mid prompt(\mathbf{x}, \{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in 1...k}))
```

```
lambda func_signature, examples: f"""
Write this function:
  def add(a, b):
Output:
  def add(a, b): return a + b
Write this function:
  def reverse(s: str) -> str:
Output:
  def reverse(s: str) -> str:
    output = ""
    for c in s:
      output = c + output
    return output
Write this function:
{func_signature}
1111111
```

(Suppose the examples are expanded into the above str)

Few-Shot Prompting prompt: str -> Examples -> str

 $Pr(\mathbf{y} \mid prompt(\mathbf{x}, \{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in 1...k}))$

```
lambda func_signature, examples: f"""
Write this function:
  def add(a, b):
Output:
  def add(a, b): return a + b
Write this function:
  def reverse(s: str) -> str:
Output:
  def reverse(s: str) -> str:
    output = ""
    for c in s:
      output = c + output
    return output
Write this function:
{func_signature}
1111111
```

k-shot (2-shot prompting shown)

(Suppose the examples are expanded into the above str)

```
fIIIII
Write this function:
  def add(a, b):
Output:
  def add(a, b): return a + b
Write this function:
  def reverse(s: str) -> str:
Output:
  def reverse(s: str) -> str:
    output = ""
    for c in s:
      output = c + output
    return output
Write this function:
  def is palindrome(s: str) -> bool:
111111
```

```
You
             Write this function:
                def add(a, b):
Language Model
def add(a, b): return a + b
                                             You
             Write this function:
                def reverse(s: str)...
Language Model
 def reverse(s: str) -> str:
   output = ""
   for c in s:
     output = c + output
   return output
                                             You
             Write this function:
                def is palindrome(s: str)
```

```
fIIIII
Write this function:
  def add(a, b):
Output:
  def add(a, b): return a + b
Write this function:
  def reverse(s: str) -> str:
Output:
  def reverse(s: str) -> str:
    output = ""
    for c in s:
      output = c + output
    return output
Write this function:
  def is palindrome(s: str) -> bool:
111111
```

```
You
              Write this function:
                def add(a, b):
Language Model (FAKE)
def add(a, b): return a + b
                                             You
              Write this function:
                def reverse(s: str)...
Language Model (FAKE)
 def reverse(s: str) -> str:
   output = ""
   for c in s:
     output = c + output
   return output
                                             You
              Write this function:
                def is palindrome(s: str)
```

```
You
              Write this function:
                def add(a, b):
Language Model
def add(a, b): return a + b
                                             You
              Write this function:
                                                    →
                def reverse(s: str)...
Language Model
 def reverse(s: str) -> str:
   output = ""
   for c in s:
     output = c + output
   return output
                                             You
              Write this function:
                def is_palindrome(s: str)
```

```
System
       You are a senior software engineer from
               a top-tier company...
                                               You
              Write this function:
                 def add(a, b):
Language Model
def add(a, b): return a + b
                                               You
              Write this function:
                 def is_palindrome(s: str)
```

```
"messages":
 { "role": "system",
    "parts": ["You are a senior software engineer from..."] },
 { "role": "user",
    "parts": ["Write this function:\ndef add(a, b):"] },
 { "role": "assistant",
    "parts": ["def add(a, b): return a + b"] },
 { "role": "user",
    "parts": ["Write this function:\ndef reverse(s: str)..."] },
 { "role": "assistant",
    "parts": ["def reverse(s: str) -> str:\n output = \"\"\n
               for c in s:\n output = c + output\n
               return output"] },
 { "role": "user",
    "parts": ["Write this function:\n
               def is_palindrome(s: str)"] }
```

```
System
       You are a senior software engineer from
                a top-tier company...
                                                You
               Write this function:
                 def add(a, b):
Language Model
def add(a, b): return a + b
                                                You
```

def is_palindrome(s: str)

Write this function:

```
"messages": [
  { "role": "system",
    "parts": ["You are a senior software engineer from..."] },
  { "role": "user",
    "parts": ["Write this function:\ndef add(a, b):"] },
 { "role": "assistant",
    "parts": ["def add(a, b): return a + b"] },
 { "role": "user",
    "parts": ["Write this function:\ndef reverse(s: str)..."] },
 { "role": "assistant",
    "parts": ["def reverse(s: str) -> str:\n output = \"\"\n
               for c in s:\n output = c + output\n
               return output"] },
  { "role": "user",
    "parts": ["Write this function:\n
               def is_palindrome(s: str)"] }
```

```
client.chat.completions.create(
   model="gpt-4o-mini",
   messages=messages
)
```

Prompting with a Conversation: Behind the Scene

Special Tokens denoting Roles

```
"messages":
  { "role": "system",
    "parts": ["You are a senior software engineer from..."] },
  { "role": "user",
    "parts": ["Write this function:\ndef add(a, b):"] },
  { "role": "assistant",
    "parts": ["def add(a, b): return a + b"] },
  { "role": "user",
    "parts": ["Write this function:\ndef reverse(s: str)..."] },
  { "role": "assistant",
    "parts": ["def reverse(s: str) -> str:\n output = \"\"\n
               for c in s:\n output = c + output\n
               return output"] },
  { "role": "user",
    "parts": ["Write this function:\n
               def is palindrome(s: str)"] }
```

```
<system>
You are a senior software engineer from...
<user>
Write this function:
  def add(a, b):
<assistant>
def add(a, b): return a + b
<user>
Write this function:
  def reverse(s: str)...
<assistant>
def reverse(s: str) -> str:
  output = ""
  for c in s:
    output = c + output
  return output
<user>
Write this function:
  def is_palindrome(s: str)
```

Does Few-Shot Learning Help LLM Performance in Code Synthesis?

Derek Xu1*, Tong Xie1*, Botao Xia1*, Haoyu Li2*

Yunsheng Bai³, Yizhou Sun¹, Wei Wang¹

¹University of California Los Angeles ²University of Illinois Urbana-Champaign ³Nvidia

* Equal Contribution

L2CEval: Evaluating Language-to-Code Generation Capabilities of Large Language Models

Ansong Ni[†] Pengcheng Yin[♣] Yilun Zhao[†] Martin Riddell[†]
Troy Feng[†] Rui Shen[†] Stephen Yin[†] Ye Liu[♦] Semih Yavuz[♠] Caiming Xiong[♠] Shafiq Joty[♠] Yingbo Zhou[♠] Dragomir Radev[†] Arman Cohan^{†‡}

[†]Yale University [‡]Allen Institute for AI [♣]Google DeepMind [♦]Salesforce Research

{ansong.ni, arman.cohan}@yale.edu

https://l2c-eval.github.io

L2CEval: Evaluating Language-to-Code Generation Capabilities of Large Language Models

Ansong Ni[†] Pengcheng Yin[♣] Yilun Zhao[†] Martin Riddell[†]
Troy Feng[†] Rui Shen[†] Stephen Yin[†] Ye Liu[♦] Semih Yavuz[♠] Caiming Xiong[♠] Shafiq Joty[♠] Yingbo Zhou[♠] Dragomir Radev[†] Arman Cohan^{†‡}


†Yale University ‡Allen Institute for AI *Google DeepMind \$\delta\$ Salesforce Research

Models	Few-Shot			Zero-Shot		
	Spider	GSM8k	MBPP	Spider	GSM8k	MBPP
Pythia-6.9B	12.5 / 33.9	2.6 / 74.5	13.2 / 97.6	2.8 / 8.0	0/0	1.2 / 15.0
Dolly-v2-7b	13.1 / 31.7	2.6 / 52.3	12.0 / 97.2	5.2 / 15.0	0/0.1	9.4 / 62.6
LLaMA-7B	13.1 / 36.1	8.0 / 71.3 3.5 / 37.1	16.6 / 96.6	5.7 / 22.2	0/0	5.0 / 29.8
Alpaca-7B	16.1 / 37.8		14.4 / 98.4	20.5 / 45.2	0/0	13.2 / 58.4
LLaMA-13B	15.2 / 41.5	15.7 / 72.7	22.8 / 97.6	15.2 / 41.6	0/0	2.2 / 7.0
Alpaca-13B	24.3 / 51.9	18.5 / 80.3	23.4 / 97.6	26.1 / 55.5	0/0	6.8 / 20.6

Table 4: How instruction-tuning affects few- and zero-shot performances. <u>Underlined models</u> are instruction-tuned from the model above them. Performance shown as "exec. acc. / exec. rate".

L2CEval: Evaluating Language-to-Code Generation Capabilities of Large Language Models

Ansong Ni[†] Pengcheng Yin[♣] Yilun Zhao[†] Martin Riddell[†]
Troy Feng[†] Rui Shen[†] Stephen Yin[†] Ye Liu[⋄] Semih Yavuz[⋄] Caiming Xiong[⋄]
Shafiq Joty[⋄] Yingbo Zhou[⋄] Dragomir Radev[†] Arman Cohan^{†‡}




··•·· code-davinci-002 --- code-cushman-001 -- CodeGen-6B-mono --- StarCoder-15.5B --- Alpaca-LoRA-7B

Prompting Language Models to "Think"



Fast, Spontaneous, Pattern-driven






Slow, Logical, Rule-driven



Prompting Language Models to "Think"



Chain-of-Thought Prompting Elicits Reasoning in Large Language Models

Jason Wei Xuezhi Wang Dale Schuurmans Maarten Bosma Brian Ichter Fei Xia Ed H. Chi Quoc V. Le Denny Zhou

Google Research, Brain Team {jasonwei,dennyzhou}@google.com

Standard Prompting

Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: The answer is 11.

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

Model Output

A: The answer is 27.



Chain-of-Thought Prompting

Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: Roger started with 5 balls. 2 cans of 3 tennis balls each is 6 tennis balls, 5 + 6 = 11. The answer is 11.

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

Model Output

A: The cafeteria had 23 apples originally. They used 20 to make lunch. So they had 23 - 20 = 3. They bought 6 more apples, so they have 3 + 6 = 9. The answer is 9. <

Augmenting Few-Shot (1-shot) with Thinking Process

Standard Prompting

Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: The answer is 11.

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

Model Output

A: The answer is 27.



Chain-of-Thought Prompting

Model Input


Q: Roger has 5 tennis balls. He buys 2 more can tennis balls. Each can has 3 tennis balls. How may tennis balls does he have now?

A: Roger started with 5 balls. 2 cans of 3 tennis b each is 6 tennis balls. 5 + 6 = 11. The answer is

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apple do they have?

Model Output

A: The cafeteria had 23 apples originally. They us 20 to make lunch. So they had 23 - 20 = 3. They bought 6 more apples, so they have 3 + 6 = 9. The answer is 9. 🗸



Large Language Models are Zero-Shot Reasoners

Takeshi Kojima

The University of Tokyo t.kojima@weblab.t.u-tokyo.ac.jp

Shixiang Shane Gu

Google Research, Brain Team

Machel Reid Google Research* Yutaka Matsuo The University of Tokyo Yusuke Iwasawa The University of Tokyo

Large Language Models are Zero-Shot Reasoners

The t.kojima@w

Machel Rei Google Resea

(a) Few-shot

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: The answer is 11.

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?

A:

(Output) The answer is 8. X

(c) Zero-shot

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?

A: The answer (arabic numerals) is

(Output) 8 X

(b) Few-shot-CoT

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: Roger started with 5 balls. 2 cans of 3 tennis balls each is 6 tennis balls. 5 + 6 = 11. The answer is 11.

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?

A:

(Output) The juggler can juggle 16 balls. Half of the balls are golf balls. So there are 16 / 2 = 8 golf balls. Half of the golf balls are blue. So there are 8 / 2 = 4 blue golf balls. The answer is 4. ✓

(d) Zero-shot-CoT (Ours)

Q: A juggler can juggle 16 balls. Half of the balls are golf balls, and half of the golf balls are blue. How many blue golf balls are there?

A: Let's think step by step.

(Output) There are 16 balls in total. Half of the balls are golf balls. That means that there are 8 golf balls. Half of the golf balls are blue. That means that there are 4 blue golf balls.

Large Language Models are Zero-Shot Reasoners

Takeshi Kojima

The University of Tokyo t.kojima@weblab.t.u-tokyo.ac.jp

Shixiang Shane Gu

Google Research, Brain Team

Machel Reid Google Research*

	Arithmetic							
	SingleEq	AddSub	MultiArith	GSM8K	AQUA	SVAMP		
zero-shot	shot 74.6/ 78.7 72.2/77.0		17.7/22.7 10.4/12.5		22.4/22.4	58.8/58.7		
zero-shot-cot	78.0/78.7	69.6/74.7	78.7/79.3	40.7/40.5	33.5/31.9	62.1/63.7		
	Common Sense		Other Reason	oning Tasks	Symbolic Reasoning			
	Common SenseQA	Strategy QA	Date Understand	Shuffled Objects	Last Letter (4 words)	Coin Flip (4 times)		
zero-shot	68.8/72.6	12.7/ 54.3	49.3/33.6	31.3/29.7	0.2/-	12.8/53.8		
zero-shot-cot	64.6/64.0	54.8 /52.3	67.5/61.8	67.5/61.8 52.4/52.9		57.6/- 91.4/87.8		

Table 4: Robustness study against template measured on the MultiArith dataset with text-davinci-002. (*1) This template is used in Ahn et al. [2022] where a language model is prompted to generate step-by-step actions given a high-level instruction for controlling robotic actions. (*2) This template is used in Reynolds and McDonell [2021] but is not quantitatively evaluated.

No.	Category	Template	Accuracy
1	instructive	Let's think step by step.	78.7
2		First, (*1)	77.3
3		Let's think about this logically.	74.5
4		Let's solve this problem by splitting it into steps. (*2)	72.2
5		Let's be realistic and think step by step.	70.8
6		Let's think like a detective step by step.	70.3
7		Let's think	57.5
8		Before we dive into the answer,	55.7
9		The answer is after the proof.	45.7
10	misleading	Don't think. Just feel.	18.8
11		Let's think step by step but reach an incorrect answer.	18.7
12		Let's count the number of "a" in the question.	16.7
13		By using the fact that the earth is round,	9.3
14	irrelevant	By the way, I found a good restaurant nearby.	17.5
15		Abrakadabra!	15.5
16		It's a beautiful day.	13.1
-		(Zero-shot)	17.7

Yo

You are tasked to write this function:

def min_cost_k_perio...(x, ...):

Before writing it, please first think step-by-step.

analyze what needs to be done and sketch out a piece of pseudo code; also verify your pseudo code with some imaginary input-output examples. Wrap your code in <code></code>.

Language Model (Actual Generation)

I will write the function min_cost_k_perio... to the specified requirements. The problem appears to be a dynamic programming challenge. The core idea is to find the minimum cost to segment...

```
<code>
def min_cost_k_perio...(x, ...):
    ...
</code>
```

You

You are tasked to write this function: def min_cost_k_perio...(x, ...):

Before writing it, please first think step-by-step. analyze what needs to be done and sketch out a piece of pseudo code; also verify your pseudo code with some imaginary input-output examples.

Language Model (Actual Generation)

I will write the function
min_cost_k_periodic_segmentation to
the specified requirements. The problem
appears to be a dynamic programming
challenge. The core idea is to find the
minimum cost to segment...

You

Good. Please go ahead and write the function.

Language Model (Actual Generation)

```
def min_cost_k_perio...(x, ...):
    ...
```

You

You are tasked to write this function: def min cost k perio...(x, ...):

Before writing it, please first think step-by-step. analyze what needs to be done and sketch out a piece of pseudo code; also verify your pseudo code with some imaginary input-output examples.

Language Model (Actual Generation)

I will write the function
min_cost_k_periodic_segmentation to
the specified requirements. The problem
appears to be a dynamic programming
challenge. The core idea is to find the
minimum cost to segment...

Two-Staged; No extra human annotation

You

Good. Please go ahead and write the function.

Language Model (Actual Generation)

```
def min_cost_k_perio...(x, ...):
    ...
```

You

You are tasked to write this function:

def min_cost_k_perio...(x, ...):

Before writing it, please first think step-by-step. analyze what needs to be done and sketch out a piece of pseudo code; also verify your pseudo code with some imaginary input-output examples.

Language Model (Actual Generation)

I will write the function
min_cost_k_periodic_segmentation to
the specified requirements. The problem
appears to be a dynamic programming
challenge. The core idea is to find the
minimum cost to segment...

Two-Staged; No extra human annotation

 $Pr(y | prompt_2(x) :: prompt_1(x) :: x)$

You

Good. Please go ahead and write the function.

Language Model (Actual Generation)

```
def min_cost_k_perio...(x, ...):
    ...
```

Structured Chain-of-Thought Prompting for Code Generation

Jia Li ♂ lijia@stu.pku.edu.cn Peking University Beijing, China

Yongmin Li Peking University Beijing, China liyongmin@pku.edu.cn Ge Li Peking University Beijing, China lige@pku.edu.cn

Zhi Jin Peking University Beijing, China zhijin@pku.edu.cn

Table 2: The Pass@k (%) of SCoT prompting and baselines on three code generation benchmarks. The numbers in red denote SCoT prompting's relative improvements compared to the SOTA baseline - CoT prompting.

Base Model	D	HumanEval		MBPP			MBCPP			
	Prompting Technique	Pass@1	Pass@3	Pass@5	Pass@1	Pass@3	Pass@5	Pass@1	Pass@3	Pass@5
ChatGPT	Zero-shot prompting	49.73	66.07	71.54	37.07	43.54	48.58	47.53	60.09	64.22
	Few-shot prompting	52.47	69.32	74.10	40.00	49.82	53.13	52.58	63.03	66.11
	CoT prompting	53.29	69.76	75.52	41.83	51.04	54.57	53.51	63.84	67.03
	SCoT Prompting	60.64	73.53	77.32	46.98	55.31	58.36	57.06	65.70	68.70
Relative Improvement		13.79%	5.40%	2.38%	12.31%	8.37%	6.95%	6.63%	2.91%	2.49%
Codex	Zero-shot prompting	40.20	61.78	68.11	27.07	43.81	47.93	40.25	54.17	60.65
	Few-shot prompting	42.93	62.96	70.10	33.17	45.72	49.62	44.12	57.65	62.45
	CoT prompting	43.79	63.41	71.56	35.66	46.57	50.11	45.79	58.92	62.56
	SCoT Prompting	49.82	66.56	75.14	38.29	50.74	53.16	48.34	60.77	64.19
Relative Improvement		13.77%	4.97%	5.00%	7.38%	8.95%	6.09%	5.57%	3.14%	2.61%

Initialize a result with -999999
 Iterate through the list of lists
 Initialize a sum with 0
 Iterate through the list
 Add the element to the sum
 Update result with the maximum of sum and result
 Divide the result by K
 Return the result

(a) Chain-of-Thought




Figure 1: The comparison of a Chain-of-Thoughts (CoT) and our Structured Chain-of-Thought (SCoT).

High Level Picture

Language model can generate syntactically bad program **Desired Program Fuzzy specifications &** prompts Functional Space of all Specification programs that can satisfy all examples Space of all type checked programs Space of all syntactically correct programs Space of all the strings

Summary

- Topics we have covered
 - Basics of decoding
 - From next token prediction to sequence prediction
 - Sampling algorithms for decoding
 - Basics of prompting
 - Crafting the prompt in specific manners to elicit behaviors in language models
 - Zero-shot prompting, Role-prompting
 - Few-shot prompting
 - Chain-of-thought (CoT prompting), along with FS-CoT & ZS-CoT
- Topics we have not covered
 - Advanced decoding (Aligning grammar, syntax, and semantics)
 - Other prompting strategies (Self-Consistency, Self-Reflection, Tree-of-thought, ...)
 - Technical details: how to evaluate correctness, how to parse LLM output, etc.
 - How is LLM trained? Why does it work? When does it not work? What do we do then?

Today

Behavioral Specification

- What should the program do?
- 1. Examples
- 2. Types (Function Signature)
- 3. Functional Specifications
- 4. Function Name (Natural Language)

Synthesis Strategy

- How do we find such a program?

Language Model Decoding and Prompting

- Sequentially decode tokens to form program
- Engineering the prompt to make the result better

Structural Specification

What is the space of the programs?

General Purpose Programming LanguagePython / ...

Week 3

- Assignment 1
 - https://github.com/machine-programming/assignment-1
 - Due next Tuesday (Sep 16), 5 days left!
- Assignment 2
 - Evaluating language models and testing different prompting strategies!
 - Will be released during the Weekend!
- Attendance:
 - Starting checking next week, will send courselore post
- Oral Presentation:
 - Start bidding topics/papers/slots from next week, will send courselore post

Recommended Readings

- A Survey on Large Language Models for Code Generation, Jiang et. al., 2024
- Is Self-Repair a Silver Bullet for Code Generation? Olausson et. al., 2024
- Automatically Correcting Large Language Models: Surveying the landscape of diverse self-correction strategies, Pan et. al., 2023
- The Curious Case of Neural Text Degeneration, Holtzman et. al., 2020
- Planning with Large Language Models for Code Generation, Zhang et. al., 2023
- Tree of Thoughts: Deliberate Problem Solving with Large Language Models, Yao et. al., 2023
- Syntactic and Semantic Control of Large Language Models via Sequential Monte Carlo, Loula et. al., 2025
- Large Language Models are Zero-Shot Reasoners, Kojima et. al., 2023
- Chain-of-Thought Prompting Elicits Reasoning in Large Language Models, Wei et. al., 2022
- Tree-of-Code: A Hybrid Approach for Robust Complex Task Planning and Execution, Li et. al., 2024
- <u>Defeating Nondeterminism in LLM Inference</u>, Horace He in collaboration with others at Thinking Machines, 2025